

Lanyard / Ribbon - ROT-H

ROT-H Series

- ★ Lanyard
- ★ Ribbon



Features

- Branded Electronic Components
- User Friendly Touch Screen
- 100% Full Oil Drum
- 4 Air Expansion Shafts
- Lanyard and Ribbon only
- Adjustable Heat Power
- Precise Temperature Control
- Carbon Brush Slip Ring
- 80% Blanket Coverage
- Blanket Auto Centering
- Adjustable lead-in bracket
- Belt off Tracking Alarm
- Overheat Alarm
- Pneumatic Tension & Pressure Control
- Adjustable Transfer Pressure
- Auto Power On/Off
- Suitable for 30gsm paper
- Import and export brackets

Specifications

Model	100% Full Drum Size (mm / inch)	Workable Width (mm / inch)	Qty of Heater	Rated Power (3 Phase 220V)	Max Amps (3 Phase 220V)	Rated Power (3 Phase 380V)	Max Amps (3 Phase 380V)	Linear Speed 30 Sec. Dwell (m & inch / min)	Felt Auto Centering	Visualization	Pneumatic Tension / Pressure
ROT-642H	420 / 16.5"	500 / 20"	15	11KW	29A	13KW	20A	2.1 / 83"			
ROT-660H	600 / 23.6"	500 / 20"	27	18KW	47A	21KW	32A	3.0 / 118"			
ROT-680H	800 / 31.5"	500 / 20"	33	21KW	55A	24KW	36A	4.0 / 157"			
ROT-942H	420 / 16.5"	800 / 31"	15	14KW	37A	17KW	26A	2.1 / 83"			
ROT-960H	600 / 23.6"	800 / 31"	27	23KW	60A	29KW	44A	3.0 / 118"			
ROT-980H	800 / 31.5"	800 / 31"	33	28KW	73A	34KW	52A	4.0 / 157"			
ROT-1242H	420 / 16.5"	1100 / 43"	15	17KW	45A	21KW	32A	2.1 / 83"			
ROT-1260H	600 / 23.6"	1100 / 43"	27	29KW	76A	35KW	53A	3.0 / 118"			
ROT-1280H	800 / 31.5"	1100 / 43"	33	34KW	89A	43KW	65A	4.0 / 157"			

Warranty policy does not apply to Blanket and Oil Drum ★

Other Parts are eligible for 15 months warranty under proper use. (Starting from the time of ETD) ★

Specifications and external appearance are subject to change without prior notice ★