

High Frequency Welding Machine

Application

- ★ Seaming solutions for all PVC materials, especially for Tarpaulin and Banner
- ★ Tape welding available

Features

- ★ Welding Length: up to 30m
- ★ Welding Width: varies by changing welding heads
- ★ High welding speed with low consumption
- ★ Higher speed with better welding results for 5K Version



ZL - 3000S



ZL - 3000S-5K

Specifications

Model	ZL-3000S	ZL-3000S-5K
Power	3 KW	5 KW
Surging Frequency	27.12 MHz ± 0.5%	27.12 MHz ± 0.6%
Cylinder Pressure	≥ 0.2 MP	≥ 0.2 MP
Welding Pressure	4-6 KG/CM ²	4-6 KG/CM ²
Welding Speed	0-5 M/Min	0-6 M/Min
Welding Thickness	3 MM(Multi Layer)	0.5 - 4 MM(Multi Layer)
Welding Width	20 MM, 30 MM, 40 MM	37 MM/Customized(10-50MM)
Table Length	6 M, can be Customized	6 M, can be Customized
Voltage	220V±10% 50/60 Hz	220V±10% 50/60 Hz
Voltage Stabilizer	220 V(150 V-260 V) 50/60Hz	220 V(150 V-260 V) 50/60Hz
Running Noise		≤75 DB
Type for Cooling	Wind Cooling	Wind Cooling
Air Pressure	6 Bar	6 Bar
Net Weight	350 KG	350 KG
Gross Weight	400 KG	400 KG
Packing Size	980MM * 1000MM * 1660MM	980MM * 1000MM * 1660MM
Net Weight - 3m Working Table	180 KG	200 KG
Gross Weight - 3m Working Table	220 KG	250 KG
Packing Dimension - 3m Working Table	3140MM * 94MM * 40MM	3140MM * 94MM * 45MM



★ All the parts are eligible for 15 months warranty under proper use. (Starting from the time of ETD)
 ★ Specifications and external appearance are subject to change without prior notice